

TRANSPORT DIMENSIONS

Length: 14.5m (47'7")
Height: 3.45m (11'4")
Width: 2.8m (9'2")
Weight (Est): 31,800kg (35.05 US Ton)

FEED CONVEYOR

Variable speed feed conveyor with hydraulic raise and lower facility for transport and maintenance
Fitted with over and under belt metal detector
Belt width: 1000mm (39")
Type: Shallow troughed

OPTIONS

- Concaves: extra coarse, medium coarse, coarse, Autosand®
- Short throw eccentric
- Feed hopper extension plates
- Feed hopper level sensor
- Product conveyor belt weigher
- Electric refuelling pump
- Hydraulic water pump
- Radio remote control

HOPPER

Fixed abrasion resistant feed hopper fitted with crash bars.
Length: 3.38m (11'1")
Width: 2.5m (8'2")
Capacity: 4.4m³ (5.75yd³)

CRUSHER

Autamax® cone crusher with all roller bearing design to minimise frictional losses and optimise crushing efficiencies. CSS can be adjusted whilst crushing.
Size (Head diameter): 1000mm (39")
Concave Standard: Medium Coarse
Max CSS: 36mm (1.4")
Min CSS (Typical): 18mm (0.7")
Adjustment System: Hydraulic
Overload protection: Automatic release

PRODUCT CONVEYOR

Belt width: 800mm (31.5")
Type: Troughed, fixed
Discharge height: 3.23m (10'7")
Dust suppression

POWER UNIT

Tier 3/Stage 3A:
Cat C9 Acert 242kW (325hp)
Clutch: HFO 314

Tier 4I/Stage 3B:
Scania DC9 70A 257kW (350hp)
Clutch: HPTO 12
Drive System: Direct, wedge belts

TRACKS

Type: Heavy duty
Width: 400mm (16")

