

**TRANSPORT DIMENSIONS**

Length: 21.9m (71'10")  
Height: 3.8m (12'6")  
Width: 3.5m (11'6")  
Weight (Est) complete plant:  
87,00kg (95.90 US Ton)  
Transported separately:  
Feed conveyor and divert chute:  
12,400kg (13.67 US Ton)  
Tracked plant: 74,600kg (82.23 US Ton)

**FEED CONVEYOR**

Variable speed feed conveyor  
Fitted with over and under belt metal detector  
Contaminated material dump facility  
Folds for maintenance and removes for transport  
Belt width: 1500mm (59")  
Type: Shallow troughed

**CRUSHER**

Automax® cone crusher with all roller bearing design  
To minimise frictional losses and optimise crushing efficiencies  
CSS can be adjusted whilst crushing  
Size (Head Diameter): 1500mm (59")  
Concave Standard: Coarse  
Max CSS: 64mm (2.5")  
Min CSS (Typical): 24mm (1.7")  
Adjustment System: Hydraulic  
Overload protection: Automatic Release

**HOPPER**

Fixed abrasion resistant feed hopper  
fitted with crash bars  
Extensions standard  
Length: 3.3m (10'10")  
Width: 4.25m (13'11")  
Capacity: 9m³ (11.8yd³)

**OPTIONS**

- Product conveyor belt weigher
- Hydraulic water pump
- Radio controlled tracks

**TRACKS**

Type: Heavy duty  
Width: 600mm (24")

**METAL  
DETRACTOR CHUTE**

**POWER UNIT**

Model: Cat C18 ACERT  
Power: 470kW (630hp)  
Clutch: HPTO 14  
Drive System: Direct, wedge belts

**PRODUCT CONVEYOR**

Belt Width: 1400mm (55")  
Type: Troughed, fixed  
Discharge height: 4.65m (15'3")  
Dust Suppression

