

## TRANSPORT DIMENSIONS

### Track Version

Length: 15.4m (50'6")  
 Height: 3.2m (10'6")  
 Width: 2.75m (9')  
 Weight (Est): 24,900kg (27.42 US Ton)

### Wheel Version

Length: 16.95m (55'7")  
 Height: 3.9m (12'8")  
 Width: 2.75m (9')  
 Weight (Est): 22,000kg (24.25 US Ton)

## OPTIONS

- Single deck vibrating grid
- Double deck vibrating grid
- Over band magnet
- Anti-roll back
- Tri-axle, roll in bogie or tandem
- Dual power
- R/C tracks
- Auto lube
- Tail conveyor
- Rubber lined catchbox
- Twin grade catchbox

## SCREENBOX

11' x 5' (3.52 x 1.5m) double deck,  
 4 bearing, free floating screen box  
 Side and end tension mesh.  
 6 top deck & 6 bottom deck spray bars.  
 150mm (6") water feed pipe

## MAIN CONVEYOR

1050mm (42") wide  
 Hydraulically adjustable  
 Wash box with spray bar

## FEEDER CONVEYOR

Width: 1050mm (42")  
 Variable speed  
**14ft Hopper**  
 8.75m<sup>3</sup> (11.44cu.yds with grid)



## CATCHBOX

Hydraulic open and close for mesh change

## SIDE CONVEYORS

650mm (26") wide  
 Individual variable speed  
 Stockpile 4.7m (15'5")

## TRACKS

Width: 500mm

## POWER UNIT

Diesel Hydraulic  
 CAT C4.4 Cylinder 83kW (111.3hp)  
 Hydraulic tank: 564 L (124 Gal)  
 Diesel tank: 336 L (74 Gal)  
 Dual power available