

TRANSPORT DIMENSIONS**Track Version**

Length: 16.56m (54'4")
 Height: 3.4m (11'2")
 Width: 3m (9'11")
 Weight (Est): 26,900kg (29.65 US Ton)

Wheel Version

Length: 16.95m (55'7")
 Height: 3.9m (12'8")
 Width: 3m (9'11")
 Weight (Est): 24,700kg (27.23 US Ton)

TAIL CONVEYOR

1,200mm (48") wide
 Stockpile: 4.2m (13'9")

OPTIONS

- Wheel or Track Mobile
- Double deck vibrating grizzly
- Radio controlled tracking
- Anti roll-back
- Dual power
- Roll-in bogie prepared
- Roll-in bogie equipped
- Quick release screen wedge tensioning
- Washing version
- Auto lubrication system
- Dust suppression

MAIN CONVEYOR

1,050mm (42") wide
 Hydraulically adjustable

SIDE CONVEYORS

650mm (26") wide
 Individual, variable speed
 Stockpile: 4.7m (15'5")

FEEDER CONVEYOR

Width: 1050mm (42")
 Variable speed

HOPPER

14ft = 8.15m³ (10.6cu. yds).
 Reject grid as standard

**SCREENBOX**

2 bearing arrangement
 Grease lubrication
 Top deck: 4.8m x 1.5m (16' x 5')
 Bottom deck: 4.3m x 1.5m (14' x 5')

TRACKS

Width 400mm

POWER UNIT

Standard: CAT 4.4 ATAAC 83kW (111hp)

Option

Option 1: CAT C4.4 ATAAC ACERT 97kW (130hp)
 Option 2: Deutz TCD 2013 LO4 125kW (168hp) Deutz
 TCD 2013 LO4 125kW (168hp)
 Hydraulic tank: 576 L (153 US Gal)
 Diesel tank: 336 L (88 US Gal)