

TRANSPORT DIMENSIONS

Length: 16.6m (54' 5")

Height: 3.33m (10'11")

Width: 3m (9'10")

2 Deck weight (Est): 26,900kg (29.65 US Ton)

3 Deck Weight (Est): 29,800 (32.85 US Ton)

SCREENBOX

Top deck 16m x 5m

Middle deck 16 x 4m

Bottom deck 14 x 5m

Spraybars fitted with brass nozzles

Galvanized walkway & handrails

OPTIONS

- Single deck vibrating grid
- Double deck vibrating grid
- Over band magnet
- Anti-roll back
- Tri-axle, roll in bogie
- R/C tracks
- Auto lube
- Tail conveyor
- Rubber lined catchbox
- Twin grade catchbox
- Dual power

CATCHBOX

Hydraulically lowering catchbox for ease of bottom deck mesh change

POWER UNIT

Diesel Hydraulic CAT 4.4 83kW (111.3hp) Standard
Hydraulic tank: 564 L (124 Gal) Diesel tank: 336 L (74 Gal)

MAIN CONVEYOR

1050mm (42") wide
Hydraulically adjustable
Wash box c/w spray bar

AUXILIARY CONVEYORS

650mm (26") wide
Individual variable speed
Stockpile 5.4m (13'1")

SIDE CONVEYOR

650mm (26") wide
Hydraulically folding side conveyors with Individual, variable speed control:
4.7m (15' 5") stockpile height

FEED CONVEYOR

Width: 1050mm (42")
Variable speed
Hopper: 14ft = 8.15m³ (10.6cu.yds)

TRACKS

Width: 500mm

