

Track Version

Length: 116.56m (54'4")

Height: 3.2m (11'2")

Width: 3m (9'11")

Weight (Est.): 29,800kg (32.85 US Ton)

Wheel Version

Length: 16.95m (55'7")

Height: 3.9m (12'8")

Width: 3m (9'11")

Weight (Est.): 27,500kg (26.64 US Ton)

OPTIONS

- Wheel or Track Mobile
- Double deck vibrating grizzly
- Radio controlled tracking
- Anti roll-back
- Dual power
- Roll-in bogie prepared
- Roll-in bogie equipped
- Quick release screen wedge tensioning
- Washing version
- Auto lubrication system
- Dust suppression
- Extended recirculation conveyor attached for transport

TAIL CONVEYOR

1200mm (48") Wide

Stockpile: 4.2m (13'9")

MAIN CONVEYOR

1050mm (42") wide

Hydraulically adjustable

SIDE CONVEYORS

650mm (26") wide

Individual, variable speed

Stockpile: 4.7m (15'5")

OVERSIZE PRODUCT CONVEYOR

650mm (26") wide

Stockpile 4.0m (13'1")

Stockpile: 4.7m
Hydraulic folding,
Patent pending**HOPPER**14ft = 8.15m³ (10.6cu.yds)
Reject grid as standard**FEEDER CONVEYOR**Width: 1050mm (42")
Variable speed**SCREENBOX**

2 bearing arrangement

Grease lubrication

Top deck: 4.8m x 1.5m (16' x 5')

Middle deck: 4.8m x 1.5m (16' x 5')

Bottom deck: 4.3m x 1.5m (14' x 5')

POWER UNIT

Standard: CAT 4.4 ATAAC 83kW (111hp)

Option 1: CAT C4.4 ATAAC ACERT 97kW (130hp)

Option 2: Deutz TCD 2013 LO4 125kW (168hp)

Hydraulic tank: 576 L (153 US Gal)

Diesel tank: 336 L (89 US Gal)

TRACKS

Width: 400mm