

TRANSPORT DIMENSIONS

Length: 17.6m (57'9")
Height: 3.45m (11'4")
Width: 3m (9'11")
Weight (Est): 37,400kg (41.22 US Ton)

TAIL CONVEYOR

1200mm (48") wide
Hydraulic folding for transport
Set-down for mesh changing
Stockpile: 4.28m (14') @ 24°
Stockpile: 5.0m (16'5") @ 30°

SCREENBOX

2 Bearing, oil lubrication
Top deck: 6.1 x 1.5m (20' x 5')
Middle deck: 6.1 x 1.5m (20' x 5')
Bottom deck: 5.55m x 1.5m (18' x 5')

MAIN CONVEYOR

1050mm (42") wide
Hydraulically adjustable

SIDE CONVEYORS

800mm (32") wide
Variable speed control
Stockpile: 5.04m (16'6")

OPTIONS

- Double deck vibrating grid
- Anti-roll back
- Dual power
- Tri-axle, roll in bogie
- Radio controlled tracks
- Dust suppression
- Extended aux conveyor
- Washing version

OVERSIZE PRODUCT CONVEYOR

Hydraulic folding stockpiler
(Eliminates crane on site)
650mm (26")
Stockpile: 4380mm (14'4")
Patent Pending

TRACKS

Width: 500mm

POWER UNIT

Standard: CAT C4.4 ATAAC ACERT 97kW (130hp)
Option: Deutz TCD 2013 LO4 125kW (168hp)
Hydraulic tank: 576 L (153 US Gal)
Diesel tank: 336 L (89 US Gal)

FEEDER CONVEYOR

Width: 1200mm (48")
Variable speed control

HOPPER

14ft = 8.15m³ (10.6cu.yds)
Reject grid as standard

