

TRANSPORT DIMENSIONS

Length: 15.65m (51'5")
 Height: 3.6m (11'10")
 Width: 3.0m (9'11")
 Weight (Est): 39,000kg (43.99 US Ton)

OVERSIZE PRODUCT CONVEYOR

800mm (26") wide
 Stockpile 4.4m (14'5")
 Angle adjustable
 Variable speed control

FEED CONVEYOR

1,200mm (48") wide
 Direct drive system
 Impact rollers beneath feedboot
 Variable speed control

TAIL CONVEYOR

1,200mm (48") wide
 Hydraulic folding for transport
 Angle adjustable
 Stockpile: 4.35m (14'3")

HOPPER

Target area: 11.67m x 1.65m (5'5" x 5'5")
 Feed in height: 2.44m (8')

OPTIONS

- Radio controlled tracking
- Anti roll-back
- Dual power
- Roll-in bogie prepared
- Roll-in bogie equipped
- Quick release screen wedge tensioning
- Auto lubrication system
- Dust suppression
- Recirc product conveyors

POWER UNIT

Diesel/hydraulic
 CAT C6.6 ACERT 129kW (173hp)
 Hydraulic tank: 787 L (209 US Gal)
 Diesel tank: 597 L (158 US Gal)

TRACKS

Width: 500mm

SIDE CONVEYORS

800mm (32") wide
 Hydraulic folding
 Stockpile: 4.4m (14'5")
 Variable speed control

3 DECK SCREENBOX

6.1m x 1.83m (20'x6') on all 3 screen decks
 2-Bearing drive system, oil lubrication
 10mm stroke
 Adjustable screen angle
 Wear resistant steel lined breaker box

