

TRANSPORT DIMENSIONS

Length: 17.87m (58'7")
 Height: 3.4m (11'2")
 Width: 3.1m (10'2")
 Weight (Est): 35,000kg (38.6 US Ton)

MID-FINES SIDE CONVEYOR

800mm (32") wide,
 Hydraulic folding
 Variable speed control
 Stockpile 4.46m (14'8")

FINES SIDE CONVEYOR

800mm (32") wide
 Hydraulic folding
 Stockpile 4.12m (13'6")

LIGHT DUTY BELT FEEDER

1300mm (51") wide, trough belt
 Variable speed control, Impact bars
 Twin, direct drive gearboxes
 Capacity: 4.33m³ (5.67 yrd³)
 Hydraulic folding, Wear resistant steel liners
 Feed height: Rear 2.69 (8'10")
 Feed height: Side 4.15m (13'7")

MID-OVER'S CONVEYOR

900mm (36") wide
 Variable speed control,
 hydraulic folding
 Stockpile 4.16m (13'8")

OVERSIZE SIDE CONVEYOR

800mm (32") wide,
 Variable speed control
 Stockpile 4.42m (14'6")
 Wear resistant steel lined chute, Impact bar

SCREENBOX

4.88m x 1.56m (16' x 5'2")
 Horizontal 3-deck triple shaft.
 Oval stroke adjustable up to 19mm (0.75")
 Oval stroke angle adjustable 30°-60°
 Wear resistant steel lined breaker box
 Marsh Mellow springs

UNDERSCREEN CONVEYOR

1200mm (48") wide

POWER UNIT

Standard: CAT 4.4 ACERT 97kW (130hp)
 Option: Deutz TCD2013 L04 125kW (168hp)
 Hydraulic tank: 576 L (153 US Gal)
 Diesel tank: 327 L (86 US Gal)

OPTIONS

- Radio controlled tracking
- Roll-in bogie prepared
- Roll-in bogie equipped
- Variable speed incline apron feeder

