

TRANSPORT DIMENSIONS

Length: 17.4m (57'1")
 Height: 3.4m (11'2")
 Width: 3.1m (10'2")
 Weight (Est): 36,000kg (39.68 US Ton)

HEAVY DUTY BELT FEEDER

1300mm (51") wide, belt
 Twin, direct drive gearboxes
 Variable speed control, Impact bars
 Capacity: 6.78m³ (8.87yd³)
 Hydraulic folding, Wear resistant steel liners
 Feed height: Rear 3.95m (13')
 Feed height: Side 4.5m (14'9")

MID-FINES SIDE CONVEYOR

800mm (32") wide
 Stockpile 4.46m (14'8")
 Variable speed control
 Hydraulic folding

MID-OVERS SIDE CONVEYOR

800mm (32") wide
 Variable speed control
 Stockpile 4.42m (14'6")
 Wear resistant steel lined chute & impact bars

POWER UNIT

Standard: CAT C4.4 ACERT 97kW (130hp)
 Option: Deutz TCD2013 L04 125kW (168hp)
 Hydraulic tank: 576 L (153 US Gal)
 Diesel tank: 327 L (86 US Gal)

**OPTIONS**

- Radio controlled tracking
- Roll-in bogie prepared
- Roll-in bogie equipped
- Variable speed incline apron feeder

FINES SIDE CONVEYOR

800mm (32") wide
 Hydraulic folding
 Stockpile 4.12m (13'6")

SCREENBOX

4.88m x 1.56m (16' x 5'2")
 Horizontal 3-deck triple shaft
 Oval stroke adjust. Up to 19mm (0.75")
 Oval stroke angle adjust 30°–60°
 Wear resistant steel lined breaker box
 Marsh Mellow springs

UNDERSCREEN CONVEYOR

1,200mm (48") wide

OVERSIZE CONVEYOR

1200mm (48") wide, impact bars
 Variable speed control, Hyd folding
 Stockpile 4.7m (15'5")

TRANSPORT DIMENSIONS

Length: 17.4m (57'1")
 Height: 3.4m (11'2")
 Width: 3.1m (10'2")
 Weight (Est): 36,000kg (39.68 US Ton)

HEAVY DUTY BELT FEEDER

1300mm (51") wide, belt
 Twin, direct drive gearboxes
 Variable speed control, Impact bars
 Capacity: 6.78m³ (8.87yd³)
 Hydraulic folding, Wear resistant steel liners
 Feed height: Rear 3.95m (13')
 Feed height: Side 4.5m (14'9")

MID-FINES SIDE CONVEYOR

800mm (32") wide
 Stockpile 4.46m (14'8")
 Variable speed control
 Hydraulic folding

MID-OVERS SIDE CONVEYOR

800mm (32") wide
 Variable speed control
 Stockpile 4.42m (14'6")
 Wear resistant steel lined chute & impact bars

POWER UNIT

Standard: CAT C4.4 ACERT 97kW (130hp)
 Option: Deutz TCD2013 L04 125kW (168hp)
 Hydraulic tank: 576 L (153 US Gal)
 Diesel tank: 327 L (86 US Gal)

**OPTIONS**

- Radio controlled tracking
- Roll-in bogie prepared
- Roll-in bogie equipped
- Variable speed incline apron feeder

FINES SIDE CONVEYOR

800mm (32") wide
 Hydraulic folding
 Stockpile 4.12m (13'6")

SCREENBOX

4.88m x 1.56m (16' x 5'2")
 Horizontal 3-deck triple shaft
 Oval stroke adjust. Up to 19mm (0.75")
 Oval stroke angle adjust 30°-60°
 Wear resistant steel lined breaker box
 Marsh Mellow springs

UNDERSCREEN CONVEYOR

1,200mm (48") wide

OVERSIZE CONVEYOR

1200mm (48") wide, impact bars
 Variable speed control, Hyd folding
 Stockpile 4.7m (15'5")