

TRANSPORT DIMENSIONS

Length: 18.99m (64'4")
 Height: 3.6m (11'10")
 Width: 3.2m (10'6")
 Weight (Est): 45,000kg (49.60 US Ton)

SCREENBOX

6.1m x 1.93m (20' x 6'4")
 Horizontal 3-deck triple shaft
 Adjustable stroke & angle
 Wear resistant steel lined breaker box
 Marsh Mellow springs

FINES CONVEYOR

Variable speed hydraulic folding
 Discharge height: 4.3m (14'2")
 Belt width: 900mm (36")

LIGHT DUTY BELT FEEDER

Belt width: 1300mm (51")
 Twin, direct drive gearboxes
 Variable speed control, Impact bars
 Hopper capacity: 4.33m³ (5.67yd³)
 Hydraulic folding, Wear resistant steel liners

MID-FINES CONVEYOR

Variable speed hydraulic folding
 Discharge height: 4.4m (14'5")
 Belt width: 900mm

MID-OVERS CONVEYOR

Variable speed hydraulic folding
 Discharge height: 4.41m (14'6")
 Belt width: 900mm (36")

OPTIONS

- Radio controlled tracking
- Dual power
- Roll-in bogie prepared
- Roll-in bogie equipped

OVERSIZE CONVEYOR

Variable speed hydraulic folding
 Discharge height: 4.4m (14'5")
 Belt width: 900mm (36")

UNDERSCREEN CONVEYOR

1500mm (59") wide

POWER UNIT

Diesel hydraulic
 CAT C6.6 Accert 151kW, (202hp)
 Hydraulic tank: 720L (190 US Gal)
 Diesel tank: 597L (158 US Gal)

OPTIONAL CONVEYOR

Length: 5.83m (19'2")
 Belt width: 900mm (36")

