

TRANSPORT DIMENSIONS

Length: 19.6m (64'5")
Height: 3.6m (11'10")
Width: 3.2m (10'6")
Weight (Est): 45,000kg (49.60 US Ton)

SCREENBOX

Horizontal 3-deck triple shaft 6.1m (20') x 1.93m (6'4")
Adjustable stroke & angle
Wear resistant steel lined breaker box
Marsh Mellow springs

MID FINES CONVEYOR

Variable speed, hydraulic folding
Discharge height: 4.4m (14'5")
Belt width: 900mm (36")



OVERSIZE CONVEYOR

Variable speed, angle adjustable
Discharge height: 4.0m (13'1")
Belt width: 1400mm (55")

HEAVY DUTY BELT FEEDER

Belt width: 1300mm (51")
Twin, direct drive gearboxes
Variable speed control, impact bars
Hopper capacity: 8.2m³ (10.7yd³)
Hydraulic folding,
Wear resistant steel liners

OPTIONS

- Radio controlled tracking
- Dual power
- Roll-in bogie prepared
- Roll-in bogie equipped
- Variable speed incline apron feeder

MID-OVERS CONVEYOR

Variable speed, hydraulic folding
Discharge height: 4.4m (14'5")
Belt width: 900mm (36")

UNDERSCREEN CONVEYOR

1500mm (59") wide

FINES CONVEYOR

Variable speed, hydraulic folding
Discharge height: 4.4m (14'5")
Belt width: 900mm (36")

POWER UNIT

Diesel hydraulic
Cat C6.6 ACERT: 151kW, (202hp)
Hydraulic tank: 720L (190 US Gal)
Diesel tank: 597L (158 US Gal)