

## TRANSPORT DIMENSIONS

### Metrotrak

Length: 13.12m (43')  
 Height: 3.2m (10'6")  
 Width: 2.4m (7'10")  
 Weight (Est): 27,200kg (29.99 US Ton)

### Metrotrak HA

Length: 13.12m (43')  
 Height: 3.2m (10'6")  
 Width: 2.4m (7'10")  
 Weight (Est): 27,800kg (30.64 US Ton)

## PRODUCT CONVEYOR

Belt width: 800mm (31.5")  
 Discharge Height: 2.9m (9'6")  
 Dust Suppression

## POWER UNIT

Model: Cat C6.6 Tier III ACERT  
 Power: 140kW (187hp)  
 Engines are available to meet both US EPA emission standards under 40 CFR 1039.625 and EU flexibly provisions of Directive 97/68/EC  
 Clutch: HFO  
 Drive System: Direct, wedge belts

## CRUSHER

High capacity single toggle jaw with aggressive throw.  
 Size: 900mm x 600mm (35" x 24")  
 Single Toggle: Yes  
 Min CSS Quarry / Recycling: 50mm (2") / 40mm (1.5")  
 Max CSS Quarry / Recycling: 125mm (5") / 125mm (5")  
 Adjustment System: Standard, Manual/HA, Hydraulic  
 HA normal max CSS: 100mm (4")  
 Configuration change required for 125mm CSS

## HOPPER

Boltless abrasion resistant feed hopper with hydraulic fold/wedges and hydraulic adjust (HA version).  
 Length: 4m (13'2")  
 Width: 1.8m (5'10")  
 Capacity: 3.6m<sup>3</sup> (4.7yds<sup>3</sup>)

## FEEDER

Spring mounted vibrating pan incorporating twin shaft vibrating unit, variable speed control and blanking mat.  
 Grizzly: 2 sections, fixed  
 Length: 3.8m (12'5")  
 Width: 0.8m (2'7")

## OPTIONS

- Dirt conveyor
- Single pole/twin pole magnet
- Radio remote control
- Belt weigher
- Hydraulic water pump
- Electric refuelling pump
- Underscreen Mesh

## TRACKS

Type: 2 Speed  
 Width: 400mm (15.7")

