

TRANSPORT DIMENSIONS

Length: 17.4m (57'11")
 Height: 3.6m (11'10")
 Width: 3.0m (10')
 Weight (Est): 39,800kg (43.87 US Ton)

FINES SIDE CONVEYOR

Variable speed, hydraulic folding
 Belt width 900mm (36")
 Discharge height: 4.25m (13'11")

FEEDER CONVEYOR

Heavy duty impact bars & Impact rollers
 Twin drive, variable speed
 Belt width: 1300mm (51")
 Optional drive speeds available

WEAR - RESISTANT HOPPER

Capacity: 10m³ (13cu. Yrds.)
 5.49m (18') x 2.7m (8'10")
 Hydraulic folding wing plates
 Feed in height
 3.36m (11') (Collapsed hopper)
 4.47m (14'8") (Rear)
 3.61m (11'10") (Side)

OVERSIZE TAIL CONVEYOR

Wear Resistant Feed Chute
 Heavy duty impact bars
 Variable speed, angle adjustable
 Discharge height: 4.88m (16')
 Belt width: 1600mm (63")

MID SIZE SIDE CONVEYOR

Variable speed, hydraulic folding
 Belt width 900mm (36")
 Discharge height: 4.25m (13'11")
 Removable for 2WS

OPTIONS

- Radio controlled tracking
- Dual power (additional electric hydraulic drive)
- Quick release screen wedge tensioning
- Auto lubrication system
- Dust suppression
- 2 or 3 way split configuration
- High capacity incline apron feeder

SCREENBOX

Incline 2-deck triple shaft
 High amplitude screenbox
 6.1m x 1.83m (20' x 6')
 Adjustable stroke & stroke angle
 Marsh Mellow springs
 Jack up screen facility
 Galvanised screen walkways

COLLECTION CONVEYOR

Belt Width: 1500mm (59")

POWER UNIT

Diesel hydraulic (Dual Power Optional)
 CAT C6.6 ACERT 151kW (203hp)
 Hydraulic tank: 720 L (190 US Gal)
 Diesel tank: 597L (158 US Gal)

VARIOUS SCREEN MEDIA

- Bofar
- Mesh
- Finger Screens
- Ball deck
- Flex mat
- Punch plate

