

TRANSPORT DIMENSIONS**XA400S**

Length: 15.2m (49'10")

Height: 3.42m (11'2")

Width: 2.8m (9'2")

Weight (Est): 44,450kg (49 US Ton)

XR400S

Length: 15.2m (49'10")

Height: 3.42m (11'2")

Width: 2.8m (9'2")

Weight (Est): 44,750kg (49.33 US Ton)

CRUSHER

High capacity single toggle jaw with aggressive throw and hydraulic adjustment. Cartridge bearings and excellent under swing jaw.

Size: 1100mm x 700mm (44" x 28")

Single Toggle: Yes

Min CSS Quarry / Recycling: 75mm (3") / 50mm (2")

Max CSS Quarry / Recycling: 125mm (5") / 125mm (5")

Adjustment system: Hydraulic adjust (XA version)

Hydraulic Release: (XR version)

HOPPER

Boltless abrasion resistant feed hopper with hydraulic struts and wedges.

Length: 4.92m (16'2")

Width: 2.4m (7'10")

Capacity: 10m³ (13.7yds³)

Support mechanism:

Hydraulic struts and wedges

FEEDER

Spring mounted vibrating pan incorporating twin shaft vibrating unit and variable speed control.

Grizzly: 2 sections, cartridge

Length: 4.1m (13'6")

Width: 1.06m (3'6")

Underscreen: Blanking mat

OPTIONS

- Deflector plate under crusher
- Dirt conveyor
- Single pole/twin pole magnet
- Radio remote control
- Belt weigher
- Electric refuelling pump
- Hydraulic water pump
- Underscreen wire mesh

PRODUCT CONVEYOR

Modular conveyor with raise/lower facility.

Belt width: 1000mm (40")

Type: Troughed, modular, hydraulic raise / lower

Discharge height: 3.9m (12'9")

Dust suppression

POWER UNIT

Drive System: Direct, wedge belts

Model: Cat C9 Tier 3/stage 3A

Power: 194kW (260hp)

Model: Scania DC9 70A Tier 4i stage 3B

Power: 202kW (275hp)

Clutch: HPTO

**TRACKS**

Type: 2 Speed

Width: 500mm (19.7")