

TRANSPORT DIMENSIONS

Length: 17.7m (58'1")
 Height: 4.18m (13'8") pre-cleaner removed
 Width: 3.2m (10'6") without dirt conveyor
 3.55m (11'8") with dirt conveyor
 Weight (Est): 72,000kg (79.37 US Ton)

PRODUCT CONVEYOR

Belt width: 1300mm (51")
 Type: Troughed, hydraulic tail end
 Discharge height: 4m (13'1")
 Dust suppression

OPTIONS

- Grizzly bars
- 800mm (2'6") wide hydraulically folding dirt conveyor
- Single pole/twin pole magnet
- Radio remote control
- Belt weigher
- Hydraulic water pump
- Product conveyor dust shroud

CRUSHER

Single Toggle Jaw with hydraulic setting adjustment
 Size: 1415 x 820 (55" x 32")
 Single Toggle
 Min CSS Recycling: 85mm (3.25")
 Min CSS Quarry: 100mm (4")
 Max CSS Quarry / Recycling: 225mm (8")

FEEDER

Spring mounted vibrating pan incorporating twin shaft vibrating unit and variable speed control
 Length: 3.25m (10'8")
 Width: 1.35m (4'5")

HOPPER

Hydraulic fold hopper with over center struts and wedge lock system
 Length: 5.89m (19'3")
 Width: 3.81m (12'6")
 Capacity: 14m³ (19yd³)

PRE-SCREEN

Double deck independent pre-screen grizzly cartridge is 75 mm spacing, various mesh options available.
 Length: 2.29m (7'6")
 Width: 1.35m (4'5")

TRACKS

Type: Heavy duty
 Width: 500mm (19.7")

POWER UNIT

Model: Cat C13 Tier III ACERT
 Power: 287kW (385hp) @ 1800rpm
 Engines are available to meet both US EPA emission standards under 40 CFR 1039.625 and EU flexibly provisions of Directive 97/68/EC
 Clutch: HPTO
 Drive System: Direct, Wedge Belts

