

TRANSPORT DIMENSIONS

Length: 13m (42'8")
 Height: 3.1m (10'2")
 Width: 2.5m (8'2")
 Weight (Est): 24,300kg (26.72 US Ton)

PRODUCT CONVEYOR

Belt Width: 800mm (31.5")
 Type: Troughed, Modular,
 Hyd Raise/lower
 Discharge height: 3.2m (10'6")
 Dust suppression

OPTIONS

- Full & half size chrome, martensitic, austenitic & ceramic blow bars
- Tine bar spacing nominal
- Blanking plates/mats for grizzly
- Underscreen wire mesh
- Single pole/twin pole magnet
- Belt scale
- Side dirt conveyor
- Refuelling pump
- Plant lighting mast
- Hydraulic water pump
- Radio remote control

CRUSHER

Impact crusher with 4 bar rotor and twin apron design
 Feed Opening: 860 x 610 (34" x 24")
 Rotor Width: 860mm (34")
 Rotor Diameter: 860mm (34")
 Adjustment System: Hydraulic Assist
 Overload Protection: Hydraulic

HOPPER

Rigid boltless abrasion resistant feed hopper
 Length: 3.45m (11'4")
 Width: 2.18m (7'2")
 Capacity: 2.3m³ (3yd³)
 Support Mechanism: Fixed

**POWER UNIT**

Model: Cat C6.6 Tier III ACERT
 Power: 186kW (250hp) @2100rpm
 Clutch: HFO
 Drive system: Direct, wedge belts

UNDERPAN FEEDER

Width: 0.6m (24")
 Length: 2m (6'7")

TRACKS

Type: Heavy duty bolt on
 Width: 400mm (15.7")

FEEDER

Spring mounted vibrating pan, twin shaft vibrating unit, variable speed control
 Grizzly: 2 sections cartridge with tines
 Length: 3.2m (10'6")
 Width: 0.8m (31.5")
 Underscreen: Blanking mat – standard