

TRANSPORT DIMENSIONS

Length: 16.22m (53'2")
 Height: 3.44m (11'2")
 Width: 3.1m (10'2")
 Weight (Est): 40,200kg (44.31 US Ton)

POST SCREEN

4.8m x 1.5m (16ft x 5ft)
 Single deck, Angle adjustable

FINES CONVEYOR

Belt width: 1400mm (55")
 Discharge height: 2.92m (9'7")
 Dust suppression
 Hydraulic raise/lower

OPTIONS

- Full & half size chrome, martensitic, austenitic & ceramic blow bars
- Grizzly cartridges
- Punch plate options 30, 45 or 60mm
- Blanking plates/mats for grizzly
- Underscreen wiremesh
- Single pole/twin pole magnet
- Belt scale
- Side dirt conveyor
- Refuelling pump
- Hydraulic water pump
- Radio remote control
- Dust hood on product conveyor

PRODUCT CONVEYOR

Belt width: 1000mm (40")
 Type: Troughed, modular,
 Discharge height: 3.45m (11'32")
 Dust suppression

CRUSHER

Impact crusher with 4 bar rotor and twin apron design
 Feed opening: 1130 x 800mm
 Rotor width: 1100mm (43")
 Rotor diameter: 1040mm (41")
 Adjustment System: Hydraulic Adjust
 Overload Protection: Hydraulic

HOPPER

Boltless abrasion resistant feed hopper
 Length: 4.04m (13'3")
 Width: 2.1m (6'11")
 Capacity: 3.6m³

FEEDER

Spring mounted vibrating pan incorporating twin shaft vibrating unit and variable speed control

Grizzly

Length: 3.87m (12'8")
 Width: 1.08m (3'6")
 Underscreen: Blanking mat
 – standard

DIRT CONVEYOR

Type: Heavy duty bolt on
 Width: 600mm (23.6")

UNDER PAN FEEDER

Length: 2.44m (8')
 Width: 900mm (39")
 Spring mounted vibrating pan

POWER UNIT

Tier 3/Stage 3A: Cat C9 Acert 261kW (350hp)
 Clutch: HFO
 Tier 4I/Stage 3B: Scania DC9 70A 257kW (350hp)
 Clutch: HPTO
 Drive System: Direct, wedge belts

TRACKS

Type: Heavy duty bolt on
 Width: 400mm (15.7")

RECIRC. CONVEYOR

Belt width: 500mm (20")
 Hydraulic Folding for transport

