

**TRANSPORT DIMENSIONS**

Length: 14.45m (47'5")  
 Height: 3.42m (11'2")  
 Width: 2.56m (8'5")  
 Weight (Est): 32,400kg (35.71 US Ton)

**FEEDER**

Spring mounted vibrating pan incorporating twin shaft vibrating unit and variable speed control.

**GRIZZLY**

Length: 3.87m (12'8")  
 Width: 1.08m (3'6")  
 Underscreen: Blanking mat – standard

**OPTIONS**

- Full & half size chrome, martensitic, austenitic & ceramic blow bars
- Grizzly cartridges
- Punch plate
- Blanking plates/mats for grizzly
- Underscreen wiremesh
- Single pole/twin pole magnet
- Belt scale
- Side dirt conveyor
- Refuelling pump
- Hydraulic water pump
- Radio remote control
- Dust hood on product conveyor

**HOPPER**

Boltless abrasion resistant feed hopper  
 Length: 4.04m (13'3")  
 Width: 2.1m (6'11")  
 Capacity: 3.6m<sup>3</sup>

**CRUSHER**

Impact crusher with 4 bar rotor and twin apron design  
 Feed opening: 1130 x 800mm  
 Rotor width: 1100mm (43")  
 Rotor diameter: 1040mm (41")  
 Blockage assist: Yes  
 Adjustment System: Hydraulic Adjust  
 Overload Protection: Hydraulic

**PRODUCT CONVEYOR**

Belt width: 1000mm (40")  
 Type: Troughed, modular,  
 Hydraulic raise/lower  
 Discharge height: 3.45m (11'32")  
 Dust suppression

**POWER UNIT**

Tier 3/Stage 3A: Cat C9 Acert 242kW (325hp)  
 Clutch: HFO  
 Tier 4I/Stage 3B: Scania DC9 70A 257kW (350hp)  
 Clutch: HPTO  
 Drive System: Direct, wedge belts

**UNDER PAN FEEDER**

Length: 2.44m (8')  
 Width: 990mm (39")  
 Spring mounted vibrating pan

**TRACKS**

Type: Heavy duty bolt on  
 Width: 400mm (15.7")

