

TRANSPORT DIMENSIONS

Length: 17.9m (58'9")
Height: 3.8m (12'6")
Width: 3.0m (9'10")
Weight: 57,000kg (63 US Ton)

PRE-SCREEN

2 bearing, 2-deck, direct drive
2.1 m x 1.3m (6' 11" x 4' 3")

HOPPER

Wear resistant hopper
Length: 3.6m (142")
Width: 2.63m (104")
Capacity: 6.6m³ (8.6 yd³)
Hydraulic folding wing plates

VIBRATING PAN FEEDER

Spring mounted vibrating pan
Twin shaft vibrators, variable speed

OPTIONS

- Dirt conveyor
- Over band magnet
- Vibrating grizzly feeder
- Belt weigher
- Refuelling pump
- Radio remote control
- Dust suppression
- Full length product conveyor
- Engine fire extinguisher system
- Blow bars, full, half sizes, high chrome, manganese etc...

IMPACT CRUSHER

Direct Drive, HFO clutch + soft start
4 bar rotor & twin apron design
Opening: 1360 x 800mm (53" x 31")
Rotor width: 1340mm (52")
Rotor diameter: 1200mm (47")
Adjustment: Hydraulic assist
Hydraulic overload protection

POWER UNIT

CAT C13 Tier III
328kW (440hp)
SCANIA DC13 70A
332kW (440hp)
CAN-bus controller

PRODUCT CONVEYOR

Belt width: 1200mm (48")
Hydraulic raise/lower
Twin pole magnet (optional)

**GRIZZLY FINES/
BY-PASS CHUTE**

DIRT CONVEYOR

Belt width: 800mm (32")
Discharge height: 3.60m (11'10")

TRACKS

4.2m Centers
Dual speed, 500mm shoes

UNDER PAN FEEDER

2.6 m x 1.36m (103" x 53")
Spring mounted vibrating pan

