

TRANSPORT DIMENSIONS

Length: 15.3m (50'3")
Height: 3.8m (12'6")
Width: 3m (9'10")
Weight (Est): 37,000kg (40,79 US Ton)

FEED CONVEYOR

Variable speed feed conveyor with hydraulic raise and lower facility for transport and maintenance. Fitted with over and under belt metal detector.
Belt width: 1300mm (51")
Type: Shallow troughed

POWER UNIT

Tier III/Stage 3A: Cat C13 ACERT 328kW (440hp)
Tier 4i/Stage 3B: Scania DC13 70A 331kW (450hp)
Clutch: HPTO 12
Drive System: Direct, Wedge Belts

HOPPER

Fixed abrasion resistant feed hopper fitted with crash bars.
Length: 3.5m (11'6")
Width: 2.8m (9'2")
Capacity: 7m³ (9.2yds³)

CRUSHER

Terex® 2050 Gear Driven VSI
Size: 2050 GD

CONFIGURATIONS:

- Open shoe table/vaulted anvils
- Open shoe table/drop in anvils
- Heavy duty 4 port rotor/drop in anvils
- Heavy duty 4 port rotor/rock shelf
- High speed 5 port rotor/drop in anvils
- High speed 5 port rotor/rock shelf

TRACKS

Type: Heavy Duty
Width: 500mm(20")

PRODUCT CONVEYOR

Belt Width: 1000mm (39")
Type: Troughed, fixed
Discharge height: 3.46m (11'4")
Dust Suppression

OPTIONS

- Feed hopper extension plates
- Feed hopper level sensor
- Product conveyor belt weigher
- Product conveyor dust shroud
- Electric refuelling pump
- Radio remote control

